www.planscape.co.uk

SOLUTION Fliptop tables

Meeting





CHARACTERISTICS

— Metal legs finishes —

WHITE

bottom view

bottom view

ALUMINIUM





brakes.

1

PEFC



Тор

- Structurex[®] Melamine-coated particle board, 25 mm thick, high density 650 kg/m3 (+/-5 %), 2 decorative sides counterbalanced with anti-reflection treatment. Rounded corners for optimum comfort.
- 2 mm thick shock-proof ABS edging, radiused and matching the top finishes.
- Metal inserts for improved tear resistance and easier assembly.
- 2 tops at choice : straight or half-moon forms.
- 70 cm deep to take up minimum space.
- 100 % PEFC tops from sustainably managed forests.
- E1 certification in compliance with standard NF EN-717-2.
- M2 fire classification.

Leg

- The structure is made up of 2 « I » metal legs connected by a beam, 70 x 40 mm cross-section, for perfect stability.
- Dimensions : D 6 x L 68,5 x H 68,5 cm (including castors).
- Available in aluminium grey (RAL 9006) and white (RAL 9016) lacquered epoxy finishes.
- Ø 75 mm castors with brakes.
- Structures equipped with buffers to protect the tops in vertical position.

Tilting system

- Extremely easy single-handed tilting using the handle.
- The tiliting system with pivoting axes is welded to the beam ans screwed under the top.
- The vertical and horizontal positions are secured by a blocking system which is unlocked by turning the handle.
- Storage of the tables by nesting the legs to save place : 19 cm per extra table in depth and 7 cm in lenght in addition to the size of the first folded table (D 70).

Connection kit

- Kit of 4 black connectors per table included to join tables together perfectly side by side.
- Fixed with wood screws in part-drilled holes.



